

3 Megapixel Compact Cube Network Camera

CB-300A Series

HDTV 1080p/720p • WiFi/3G/4G Wireless Connection • PoE




- Most Intelligent, Compact and Affordable 3M Camera
- HDTV Quality (Full HD 1080p @ 30fps Streaming)
- Unique Design for Low Lux Application (1/2.5" Sensor)
- Intelligent Multi-Profile Sensor Management for Different Environment
- Support 802.11a/b/g/n Dual Band Wireless Connectivity
- WPS Supported for Easy Wireless Network Setup
- Support 3G/ 4G (WiMAX/LTE) Wireless Connectivity
- Interchangeable CS Mount Lens
- Edge Recording/ Micro SD slot
- PoE/ Two-way Audio/ PIR/ Illumination LED/ DIDO/ Privacy button



Photo Indication & Dimension Diagram



- | | |
|-------------------------------|---------------------------|
| 1 Adjustable focal Lens (*) | 11 WPS button (*) |
| 2 Built-in Microphone | 12 Privacy button |
| 3 PIR | 13 Power LED |
| 4 Illumination LED | 14 Status LED |
| 5 Speaker | 15 Internet LED |
| 6 Power Connector | 16 WPS LED (*) |
| 7 Ethernet RJ45 Socket | 17 Privacy LED |
| 8 Reset Button | 18 USB Port for 3G/4G (*) |
| 9 DIDO Terminal I/O Connector | |
| 10 Micro SD/SDHC slot | |
- * These are optional features **



Camera

Models	CB-300Ap Board Lens, USB for 3G, PoE WCB-300Ap Board Lens, WiFi CB-302Ap CS Mount Lens, USB for 3G, PoE WCB-302Ap CS Mount Lens, WiFi
Hardware System	CPU: 533 MHz Flash: 32M RAM: 256M DDR
Image Sensor	Sensor Type : 1/2.5" CMOS Sensor Sensor Resolution : 2048x1536 pixel
Minimum Illumination	CB-300Ap/ WCB-300Ap 1 lux (F2.8, B/W) / 2 lux (F2.8, Color) CB-302Ap/ WCB-302Ap 1 lux (F1.5, B/W) / 2 lux (F1.5, Color)
Lens	CB-300Ap/ WCB-300Ap Lens Type: Board Lens Focal Length: f= 6.34 mm Iris: F2.8 View Angle: (H): 40°/ (V): 30°/ (D): 50° CB-302Ap/ WCB-302Ap Lens Type: CS Mount Lens Focal Length: f= 4.05 mm Iris: F1.5 View Angle: (H): 63°/ (V): 48°/ (D): 78°

Audio

Audio Streaming	2-way Audio Support
Audio Compression	G.711, AMR (8 kHz, Mono, PCM)
Audio Input/ Output	Built-in MIC & Speaker

Video

Video Image Compression	H.264 / MPEG4 / MJPEG
Video Setting	Audio Exposure Control: Sport/ Normal/ Night Vision/ User Defined Manual Exposure Control: 1/20000~1/5s Manual Gain Control: 1X ~ 32X Manual White Balance Control: 2000K~7000K
S/N Ratio	38.1 dB
Image Resolution	3M : 2048x1536 @ 18fps 2M (Full HD) : 1920x1080 @ 30fps 1M (HDTV) : 1280x720 @ 30fps

General

Communication	Ethernet : one 10/100Mbps RJ-45 Supported Protocols : TCP/IP, UDP, ICMP, DHCP, NTP, DNS, DDNS, SMTP, FTP, HTTP, HTTPs, Samba, PPPoE, UPnP, RTP, RTSP, RTCP, IPv4, IPv6, 802.1x
Power Input	DC12V/ 1A(Power Supply)
Max. Power Consumption	CB-300Ap/CB-302Ap : 4.2 watts WCB-300Ap/WCB-302Ap : 4.6 watts
Environment	Operating Temperature 0°C ~ 50°C (32°F ~122°F), Operating Humidity : 10% ~ 80%
Dimension	34.8 (L) X60 (W) X 95 (H) mm
Weight	CB-300Ap : 99g WCB-300Ap : 106g CB-302Ap : 122g WCB-302Ap : 129g
Certification	FCC, CE
Warranty	Limited 2-year warranty

CB-300A Series	CB-300Ap	WCB-300Ap	CB-302Ap	WCB-302Ap
Interchangeable CS-Mount Lens			✓	✓
Wireless (11a/b/g/n dual band WiFi)		✓		✓
Wired (802.3af PoE)	✓		✓	
USB port for 3G/ 4G(WiMAX/LTE)	✓		✓	
DIDO I/O Port	✓	✓	✓	✓

Work Best With

Camera Accessories Options



M13VM288IR
2.2x Vari-focal Lens with Manual Iris



CI-803A/CI-803C
Camera Bracket



GL-222
Camera Bracket

Network Equipment Options



PS-588I-v3
8-port 10/100M PoE Fast Ethernet Switch